



⚠ ATTENZIONE

MANUALE D'ISTRUZIONI

FARETTO DA SOFFITTO ORIENTABILE IP20




Si raccomanda di rivolgersi a un elettricista qualificato per installare il prodotto.

Le lampade 12V necessitano di un trasformatore (non incluso).


Staccare la corrente prima dell'installazione.

Usare dei guanti o un panno quando si maneggia la lampada o l'apparecchio, in quanto possono diventare caldi o causare ustioni.

MONTAGGIO



1. Scollegare la corrente elettrica. Separare la base del faretto ed effettuare i fori sul soffitto.



2. Fissare la lampada sul portalampade GU10, collegare i fili al morsetto.


Specifiche tecniche:

	MISURE	MAX W	AC/Hz	FORMA	FINITURA	CLASSE	IK
IPC10RB	Ø93,5*100mm	11	AC 220V Hz 50/60	ROTONDO	BIANCO	II	06
IPC10RN	Ø93,5*100mm	11	AC 220V Hz 50/60	ROTONDO	NERO	II	06
IPC10QB	93,5*100mm	11	AC 220V Hz 50/60	QUADRATO	BIANCO	II	06
IPC10QN	93,5*100mm	11	AC 220V Hz 50/60	QUADRATO	NERO	II	06


Faretto da soffitto orientabile rotondo e quadrato in policarbonato per lampada GU10 (non inclusa). Disponibile in due finiture: bianca e nera. Resistente agli urti.

1

2



3. Fissare il faretto alla base con le viti e chiudere il porta faretto.



4. Il faretto è pronto all'uso.

Informazioni sul riciclaggio in conformità con le direttive RAAE e batterie




Simbolo sul prodotto



Simbolo sulla batteria

Solo Europa

Il prodotto/batteria è contrassegnato con uno dei simboli di riciclaggio sopra indicati. Questo indica che a fine vita il prodotto/batteria, dovrà essere smaltito/a separatamente in appropriati luoghi di raccolta e non con i normali rifiuti domestici.



IPERLUX®
www.iperlux.com
info@iperlux.com

INSTRUCTION MANUAL ADJUSTABLE CEILING SPOTLIGHT IP20




Specifications and Technical Data sheet:


	SIZE	MAX W	AC/Hz	SHAPE	FINISH	CLASS	IK
IPC10RB	Ø93,5*100mm	11	AC 220V Hz 50/60	ROUND	WHITE	II	06
IPC10RN	Ø93,5*100mm	11	AC 220V Hz 50/60	ROUND	BLACK	II	06
IPC10QB	93,5*100mm	11	AC 220V Hz 50/60	SQUARE	WHITE	II	06
IPC10QN	93,5*100mm	11	AC 220V Hz 50/60	SQUARE	BLACK	II	06

Adjustable round and square PC ceiling lamp holder for GU10 bulb (not included). Available in two finishes: white and black. Resistant to impacts.

1



- Secure the spotlight to the base with screws and close the spotlight holder.



- The spotlight is ready to use.

⚠ WARNING


It is recommended to contact a qualified electrician to install the product.

12V lamps require a transformer (not included).


Turn off the power before installation.

Use gloves or a cloth when handling the lamp or the spotlight, as they can become hot or cause burns.

MOUNTING



- Disconnect the electricity. Separate the base of the spotlight and drill holes in the ceiling.



- Attach the lamp to the GU10 lamp holder, connect the wires to the clamp.

2

Recycling Information in Accordance with the WEEE and Battery Directives




Product Mark



Battery Mark

Europe only

The product/battery is marked with one of the above recycling symbols. It indicates that at the end of the life of the product/battery, you should dispose of it separately at an appropriate collection point and not place it in normal domestic waste stream.



IPERLUX®
www.iperlux.com
info@iperlux.com