


# BORA BORA

Sorgente 3CCT (3000K/4000K/6500K).  
 Voltaggio 180-250V.  
 Corpo e cover in polycarbonato autoestinguente V2 e staffa in lega di alluminio.  
 Resistente alla prova del filo incandescente per 650°C.  
 Disponibile in quattro finiture: bianco, corten, grigio e nero.

LED CCT sources (3000K/4000K/6500K).  
 Voltage 180-250V.  
 V2 self-extinguishing PC housing and cover and aluminium alloy bracket.  
 Glow wire tested at 650°C.  
 Available in four finishes: white, corten, grey and black.



|          |       |             |               |         |        |              |               |       |         |  |  |  |
|----------|-------|-------------|---------------|---------|--------|--------------|---------------|-------|---------|--|--|--|
| LED LAMP | IP 65 | AC 180-250V | $\alpha$ 120° | CRI >80 | PF 0,9 | HOURS 25.000 | TEMP -20+50°C | IK 08 | UV free |  |  |  |
|----------|-------|-------------|---------------|---------|--------|--------------|---------------|-------|---------|--|--|--|



|             |         |
|-------------|---------|
| Temperatura | 3CCT    |
| Potenza     | 20W     |
| Lumen       | 2050 Lm |
| Confezione  | 20 pz   |

Codice  
 ● IPB20LWGS

