IPERLUX®

MANUALE D'ISTRUZIONI

TRACK LIGHT TRIFASE 3CCT



NEUTRA

Specifiche tecniche:

	MISURE	W	Lumen	AC/Hz	3CCT (SWITCH)	CRI	TEMP. LAVORO	FINITURA	FLICKER	DIMM.	CLASSE	IK
IP10TR36BS	Ø54*168,09mm	10	1000	AC180-250V Hz 50/60	3000/4000/6500K	80	-20°+50°	BIANCO	FREE	NO	I	06
IP10TR36NS	Ø54*168,09mm	10	1000	AC180-250V Hz 50/60	3000/4000/6500K	80	-20°+50°	NERO	FREE	NO	I	06
IP15TR36BS	Ø54*183,09mm	15	1500	AC180-250V Hz 50/60	3000/4000/6500K	80	-20°+50°	BIANCO	FREE	NO	I	06
IP15TR36NS	Ø54*183,09mm	15	1500	AC180-250V Hz 50/60	3000/4000/6500K	80	-20°+50°	NERO	FREE	NO	I	06
IP20TR36BS	Ø63*193,09mm	20	2000	AC180-250V Hz 50/60	3000/4000/6500K	80	-20°+50°	BIANCO	FREE	NO	I	06
IP20TR36NS	Ø63*193,09mm	20	2000	AC180-250V Hz 50/60	3000/4000/6500K	80	-20°+50°	NERO	FREE	NO	I	06
IP30TR36BS	Ø76*238,09mm	30	3000	AC180-250V Hz 50/60	3000/4000/6500K	80	-20°+50°	BIANCO	FREE	NO	I	06
IP30TR36NS	Ø76*238,09mm	30	3000	AC180-250V Hz 50/60	3000/4000/6500K	80	-20°+50°	NERO	FREE	NO	I	06

Un'illuminazione d'accento pensata per ambienti che richiedono non solo performance luminose superiori ma anche un impatto estetico distintivo.
Corpo in alluminio autoestinguente V2 e lente in policarbonato, resistente alla prova del filo per 650°C. Disponibile in due finiture: bianco e nero. Resistente agli urti.

⚠ ATTENZIONE

Si raccomanda di rivolgersi a un elettricista qualificato per installare il prodotto.

Si raccomanda di non toccare il prodotto quando è acceso.

In caso di malfunzionamento, staccare la lampada dall'alimentazione.
Si raccomanda di rivolgersi a un elettricista e di non provare a riparare la lampada da soli.

MONTAGGIO



1. Scollegare la corrente elettrica.



2. Spostare il bottone nella posizione verticale per installare il track.



3. Selezionare la temperatura colore.



4. Inserire la scatola elettrica nel binario e ruotare il bottone nella posizione orizzontale.



5. Fissare il prodotto al binario e accendere la corrente.

ACCESSORI CORRELATI (NON INCLUSI):





IPADTRBS - IPADTRNS
Adattatore a superficie





IPADTRBR - IPADTRNR
Adattatore a incasso

Informazioni sul riciclaggio in conformità con le direttive RAAE e batterie



Simbolo sul prodotto



Simbolo sulla batteria

Solo Europa

Il prodotto/batteria è contrassegnato con uno dei simboli di riciclaggio sopra indicati. Questo indica che a fine vita il prodotto/batteria, dovrà essere smaltito/a separatamente in appropriati luoghi di raccolta e non con i normali rifiuti domestici.

CE RoHs



IPERLUX®
www.iperlux.com
info@iperlux.com

IPERLUX®

INSTRUCTION MANUAL

CCT TRI-PHASE TRACK LIGHT



NEUTRA

Specifications and Technical Data sheet:

	SIZES	W	LUMEN	AC/Hz	3CCT (SWITCH)	CRI	AMB. TEMP.	FINISH	FLICKER	DIMM.	CLASS	IK
IP10TR36BS	Ø54*168,09mm	10	1000	AC180-250V Hz 50/60	3000/4000/6500K	80	-20°+50°	WHITE	FREE	NO	I	06
IP10TR36NS	Ø54*168,09mm	10	1000	AC180-250V Hz 50/60	3000/4000/6500K	80	-20°+50°	BLACK	FREE	NO	I	06
IP15TR36BS	Ø54*183,09mm	15	1500	AC180-250V Hz 50/60	3000/4000/6500K	80	-20°+50°	WHITE	FREE	NO	I	06
IP15TR36NS	Ø54*183,09mm	15	1500	AC180-250V Hz 50/60	3000/4000/6500K	80	-20°+50°	BLACK	FREE	NO	I	06
IP20TR36BS	Ø63*193,09mm	20	2000	AC180-250V Hz 50/60	3000/4000/6500K	80	-20°+50°	WHITE	FREE	NO	I	06
IP20TR36NS	Ø63*193,09mm	20	2000	AC180-250V Hz 50/60	3000/4000/6500K	80	-20°+50°	BLACK	FREE	NO	I	06
IP30TR36BS	Ø76*238,09mm	30	3000	AC180-250V Hz 50/60	3000/4000/6500K	80	-20°+50°	WHITE	FREE	NO	I	06
IP30TR36NS	Ø76*238,09mm	30	3000	AC180-250V Hz 50/60	3000/4000/6500K	80	-20°+50°	BLACK	FREE	NO	I	06

An accent lighiting solution designed for spaces that require not only superior lighting performances but also a distinctive aesthetic impact.
ANTI-UV and V2 Self-estinguishing aluminium housing and PC lens. Glow wire tested at 650°C. Available in two finishes: white and black. Resistant to impacts.

⚠ WARNING

It is recommended to contact a qualified electrician to install the product.

It is recommended not to touch the product when it is turned on.

In case of malfunction, disconnect the lamp from the power supply.
It is recommended to contact an electrician and not try to repair the lamp yourself.

MOUNTING



1. Switch off the power.



2. Turn the button to the vertical position to install the track light.



3. Select the color temperature.



4. Insert an electric box into the line and rotate the button to the horizontal position.



5. Fit the product to the track light and switch on the light.

SUITABLE ACCESSORIES (NOT INCLUDED):



IPADTRBS - IPADTRNS
Ceiling adapter

IPADTRBR - IPADTRNR
Recessed adapter

Recycling Information in Accordance with the WEEE and Battery Directives



Product Mark Battery Mark

Europe only

The product/battery is marked with one of the above recycling symbols. It indicates that at the end of the life of the product/battery, you should dispose of it separately at an appropriate collection point and not place it in normal domestic waste steam.

CE RoHs

IPERLUX®
www.iperlux.com
info@iperlux.com