IPERLUX®

MANUALE D'ISTRUZIONI

TRACK LIGHT TRIFASE PER LAMPADE GU10



ANDŌ

Specifiche tecniche:

	MISURE	MAX W	VOLTAGGIO	ATTACCO	FINITURA	IK	CLASSE
IPGU10TRB	Ø57*165mm	15	AC180-250V 50-60Hz	GU5.3/GU10/MR16	BIANCO	06	I
IPGU10TRN	Ø57*165mm	15	AC180-250V 50-60Hz	GU5.3/GU10/MR16	NERO	06	I

Un'illuminazione d'accento pensata per ambienti che richiedono non solo performance luminose superiori ma anche un impatto estetico distintivo.
Corpo in alluminio autoestinguente V2 e lente in policarbonato, resistente alla prova del filo per 650°C. Disponibile in due finiture: bianco e nero. Resistente agli urti.
Adattatore GU10 incluso, lampada non inclusa.


⚠ ATTENZIONE

Si raccomanda di rivolgersi a un elettricista qualificato per installare il prodotto.


Si raccomanda di non toccare il prodotto quando è acceso.

In caso di malfunzionamento, staccare la lampada dall'alimentazione.
Si raccomanda di rivolgersi a un elettricista e di non provare a riparare la lampada da soli.


MONTAGGIO




1. Scollegare la corrente elettrica.




2. Svitare il prodotto.



3. Inserire la lampada nel prodotto.



4. Avvitare il prodotto.



5. Fissare il prodotto al binario e accendere la corrente.

ACCESSORI CORRELATI (NON INCLUSI):



IPADTRBS - IPADTRNS
Adattatore a superficie



IPADTRBR - IPADTRNR
Adattatore a incasso

Informazioni sul riciclaggio in conformità con le direttive RAAE e batterie



Simbolo sul prodotto



Simbolo sulla batteria

Solo Europa

Il prodotto/batteria è contrassegnato con uno dei simboli di riciclaggio sopra indicati. Questo indica che a fine vita il prodotto/batteria, dovrà essere smaltito/a separatamente in appropriati luoghi di raccolta e non con i normali rifiuti domestici.

CE RoHs

IPERLUX®
www.iperlux.com
info@iperlux.com

IPERLUX®

INSTRUCTION MANUAL

TRI-PHASE TRACK LIGHT FOR GU10 BULB.



ANDŌ

Specifications and Technical Data sheet:

	SIZE	MAX W	VOLTAGE	BULB	FINISH	IK	CLASSE
IPGU10TRB	Ø57*165mm	15	AC180-250V 50-60Hz	GU5.3/GU10/MR16	WHITE	06	I
IPGU10TRN	Ø57*165mm	15	AC180-250V 50-60Hz	GU5.3/GU10/MR16	BLACK	06	I

An accent lighiting solution designed for spaces that require not only superior lighting performances but also a distinctive aesthetic impact.
V2 Self-estinguishing aluminium housing.
Glow wire tested at 650°C. Available in two finishes: white and black. Resistant to impacts.
GU10 adapter included, bulb not included.


⚠ WARNING

It is recommended to contact a qualified electrician to install the product.


It is recommended not to touch the product when it is turned on.

In case of malfunction, disconnect the lamp from the power supply.
It is recommended to contact an electrician and not try to repair the lamp yourself.


MOUNTING




1. Switch off the power.




2. Unscrew the product.



3. Insert the bulb.



4. Screw the product.



4. Screw the product.
5. Fit the product to the track light and switch on the light.

SUITABLE ACCESSORIES (NOT INCLUDED):



IPADTRBS - IPADTRNS
Ceiling adapter



IPADTRBR - IPADTRNR
Recessed adapter

Recycling Information in Accordance with the WEEE and Battery Directives



Product Mark



Battery Mark

Europe only

The product/battery is marked with one of the above recycling symbols. It indicates that at the end of the life of the product/battery, you should dispose of it separately at an appropriate collection point and not place it in normal domestic waste steam.

CE RoHs

IPERLUX®
www.iperlux.com
info@iperlux.com